
FEATURES/BENEFITS

For residential and light commercial water softener/filtration applications
Slim diameter with capacities from 2 to 85 gallons
Unmatched strength and chemical resistance
5-year warranty for 7 in. - 21 in. vessels

MATERIAL OF CONSTRUCTION

Inner shell of high density polyethylene
Threaded inlet in various sizes: 2.5 in. 4 in.

APPLICATIONS

Residential/light commercial softening
Residential/light commercial filtration
Portable exchange tanks

OPERATING PARAMETERS

Maximum operating pressure - 150 psi
Maximum operating temperature - 120° F

PENTAIR DESIGN PARAMETERS

Safety factor - 4:1
Minimum burst at 600 psi
Tested to 250,000 cycles without leakage

COLOR OPTIONS

GR - Gray NA - Natural
BL - Blue BK - Black



SPECIFICATIONS FOR PE LINER TANKS


Vessel Dia.	Tank Size		Opening		Total height		Diameter	Capacity		Base
	in.	mm.	Top	Bottom	LA	mm.	mm.	Gal.	Lit.	
7 in.	7×17	180×430	2.5in.	N/A	431		185	2.3	8.6	Standard
	7×35	180×905	2.5in.	N/A	906		185	5.2	19.7	Standard
	7×44	180×1130	2.5in.	N/A	1128		185	6.7	25.4	Standard
8 in.	8×17	205×445	2.5in.	N/A	432		210	3.0	11.4	Standard
	8×35	205×905	2.5in.	N/A	901		210	6.6	25.0	Standard
	8×44	205×1130	2.5in.	N/A	1133		210	8.7	32.9	Standard
9 in.	9×35	230×905	2.5in.	N/A	904		233	8.3	31.4	Standard
	9×42	230×1085	2.5in.	N/A	1071		233	10.1	38.2	Standard
	9×48	230×1230	2.5in.	N/A	1247		233	11.8	44.7	Standard
10 in.	10×35	255×905	2.5in.	N/A	908		258	10.2	38.6	Standard
	10×40	255×1020	2.5in.	N/A	1024		258	11.7	44.3	Standard
	10×44	255×1130	2.5in.	N/A	1139		258	13.1	49.6	Standard
	10×54	255×1390	2.5in.	N/A	1390		258	16.4	62.1	Standard
12 in.	12×48	300×1235	2.5in.	N/A	1231		306	20.6	78.0	Standard
	12×52	300×1340	2.5in.	N/A	1328		306	22.2	84.0	Standard
13 in.	13×54	330×1400	2.5in.	N/A	1366		333	27.0	102.2	Standard
14 in.	14×65	355×1670	2.5in.	N/A	1656		370	38.0	143.8	Standard
	14×65	355×1670	4in.	N/A	1660		370	38.0	143.8	Standard
16 in.	16×65	400×1670	2.5in.	N/A	1671		409	49.0	185.5	Standard
	16×65	400×1670	4in.	N/A	1677		409	49.0	185.5	Standard
18 in.	18×65	450×1670	4in.	N/A	1693		472	64.0	242.3	SMC
21 in.	21×62	535×1690	4in.	N/A	1705		557	82.4	312.0	SMC
	21×62	535×1690	4in.	4in.	1949		557	82.4	312.0	TRIPOD

* Measurements are subject to change without notice and are for reference only.


* Please refer the individual drawing for dimension, volumes and weight etc.




Detail 2.5 in. opening



Detail 4 in. opening



Detail base



Pentair Water (SuZhu) Co., Ltd

No.371, He Shan RD, Suzhou, Jiangsu Province, China TEL: 86-512-66617690 FAX: 86-512-66618853 <http://www.pentairaqua.com>

Pentair Residential Filtration, LLC

5730 North Glen Park Road, Milwaukee, WI 53209, USA TEL: 262.238.4400 FAX: 262.238.4404 Customer Care: 800.279.9404

All Pentair trademarks and logos are owned by Pentair, Inc. All other brand or product names are trademarks or registered marks of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice.

Pentair is an equal opportunity employer.

0616 Rev B JUL15 © 2015 Pentair Residential Filtration, LLC. All Rights Reserved.